

CRITERIA-1D

Technical manual



(Draft 2022.01)

Fausto Tomei ftomei@arpae.it

Gabriele Antolini gantolini@arpae.it

Giulia Villani gvillani@arpae.it

Marco Bittelli marco.bittelli@unibo.it



SUMMARY

SUMMARY

0. INTRODUCTION

1. DATA

1.1 Projects

1.2 db_meteo

1.2.1 Table meteo_locations

1.2.2 Weather data tables

1.3 db_soil

1.3.1 Table soils

1.3.2 Table horizons

1.4 db_crop

1.4.1 Table crop_class

1.4.2 Table crop

1.4.3 Crop parameters description

1.5 db_unit

1.6 db_output

2. ALGORITHMS

2.1 Water

2.1.1 Water retention curve

2.2 Water flow numerical model

2.3 Layer-based empirical model

2.3.1 Maximum infiltration

2.3.2 Infiltration and redistribution

2.3.3 Surface and subsurface runoff

2.3.4 Capillary rise

2.4 Crop

2.4.1 Potential evapotranspiration

2.5 Irrigation

CRITERIA references

Other references

0. INTRODUCTION

CRITERIA-1D is an agro-hydrological model simulating one-dimensional soil water fluxes, crop development and crop water needs. The soil and crop parameters can be defined at different levels of detail. It requires as input daily agro-meteorological data: minimum and maximum air temperature, total precipitation and, if available, data of water table depth to estimate the capillary rise. The software is written in C++ using Qt libraries, so cross-platform building is possible (Windows, Linux, Mac OS).

1. DATA

CRITERIA-1D input and output data are stored in SQLite databases (.db files) that can be easily managed by open source software on main platforms (Windows, Linux or MacOS), such as [sqlitebrowser](#).

1.1 Projects

Data are typically organized in projects (/DATA/PROJECT/projectName), with a directory for each project, containing a settings file *projectName.ini* and a subdirectory *data*. You can see the [test project](#) in the distribution as an example.

Projects can be opened by loading the corresponding project.ini in the **CRITERIA1D_PRO** graphical user interface (*File→Open Project*). With the same interface it is possible to create a new project (*File→New Project*) and execute a single case of the project (*File→Execute Case*). All cases of a project can be executed in a command shell passing the .ini file as parameter to the **CRITERIA1D** executable (e.g. Bash shell in Linux, DOS shell in Windows).

The project.ini file must contain the following information:

- [project] section: the location referring to the input/output data
- [output] section: additional output that the user requires, which will be added to the default output of the model.

The file path of input/output data can be absolute or relative to the location of the project.ini file. If the *db_output directory* is missing, it will be created at the first project run.

Below is an example of the structure of a settings file (**test.ini**). In the following section, the structure of each input and output file will be described.

```
[software]
software="CRITERIA1D"

















[project]
path="."
name="test"
db_meteo="./data/meteo.db"
```

```
db_soil="./data/soil_ER_2002.db"
db_crop="./data/crop.db"
db_units="./data/units.db"
db_output="./output/test.db"
```

```
[output]
waterContent=15,30,50
waterPotential=15,30,50
```

1.2 db_meteo

Weather dataset is organized in a SQLite database with a **meteo_locations** table and several weather data tables.

Nome	Tipo	Schema
▼  Tabelle (2)		
▼  data_example		CREATE TABLE "data_example" ("date" TEXT, "tmin" REAL, "tmax"
 date	TEXT	"date" TEXT
 tmin	REAL	"tmin" REAL
 tmax	REAL	"tmax" REAL
 tavg	REAL	"tavg" REAL
 prec	REAL	"prec" REAL
 etp	REAL	"etp" REAL
 watertable	REAL	"watertable" REAL
▼  meteo_locations		CREATE TABLE "meteo_locations" ("id_meteo" TEXT, "table_name"
 id_meteo	TEXT	"id_meteo" TEXT
 table_name	TEXT	"table_name" TEXT
 meteo_name	TEXT	"meteo_name" TEXT
 longitude	REAL	"longitude" REAL
 latitude	REAL	"latitude" REAL
 height	REAL	"height" REAL

*Example of **meteo.db** structure*

A **template_meteo.db** is available in the directory [DATA/TEMPLATE](#) and an example of **meteo.db** in the test project [DATA/PROJECT/test/data](#)

1.2.1 Table meteo_locations

meteo_locations table contains the locations and properties of the meteo points or the cells of a gridded meteorological dataset. The table contains the following fields:

- *id_meteo*: point/cell identifier;
- *table_name*: name of the table, for example composed by "GRD_" followed by the grid cell identifier;
- *meteo_name*: location name;
- *longitude*: longitude of the cell center in the WGS84 geographic reference system (decimal degrees);

- *latitude*: latitude of the cell center in the WGS84 geographic reference system (decimal degrees);
- *height* (optional): height of the cell center (meters);

id_meteo	table_name	meteo_name	longitude	latitude	height
Filter	Filter	Filter	Filter	Filter	Filter
01878	GRD_01878	VALSAVIGNONE	12.033825	43.7325	816.26
01918	GRD_01918	MONTE DELLA ZUCCA	12.096875	43.7325	915.44
01958	GRD_01958	SAN PATRIGNANO	12.159925	43.7325	781.15
01998	GRD_01998	POGGIO DELLE CAMPANE	12.222975	43.7325	575.14
01797	GRD_01797	BADIA PRATAGLIA	11.907725	43.7775	979.62
01837	GRD_01837	VERGHERETO	11.970775	43.7775	844.81

*Example of **meteo_locations** table*

1.2.2 Weather data tables

The other tables of the **meteo** database contain the meteorological data, one table for each meteo point (or for each cell of the analysis grid). The name of each table must correspond to the field *table_name* in **meteo_locations**.

The meteorological data are organized according to the following format:

- *date*: ISO8601 format (YYYY-MM-DD) *
- *tmin*: daily minimum air temperature (°C) *
- *tmax*: daily maximum air temperature (°C) *
- *tavg* (optional): daily average air temperature (°C)
- *prec*: daily total precipitation (mm) *
- *et0* (optional): reference evapotranspiration (mm)
- *watertable* (optional): water table depth (m)

* required data

date	tmin	tmax	tavg	prec	et0	watertable
Filtro	Filtro	Filtro	Filtro	Filtro	Filtro	Filtro
2012-01-01	1.9	7.9	4.6	0	NULL	NULL
2012-01-02	2.8	7.2	4.6	8.4	NULL	NULL
2012-01-03	2.6	6.9	4.9	0	NULL	NULL
2012-01-04	2.1	3.9	2.7	0	NULL	NULL
2012-01-05	1.5	10.8	5.6	2.6	NULL	NULL
2012-01-06	5.4	9.7	6.9	0	NULL	NULL
2012-01-07	5.2	11.4	7.7	0	NULL	NULL

Example of a weather data table

If potential evapotranspiration is not available, the model will estimate the variable by means of the Hargreaves-Samani equation using daily temperatures and latitude. If water table depth is missing the model will simulate a free drainage condition at the soil bottom.


1.3 db_soil

Soil data and parameters are organized in several tables: **soils**, **horizons**, **driessen**, **van_genuchten** and **water_retention**. The **UNITS** table lists the measurement units of each field in the soil database.

A **template_soil.db** is available in the directory [DATA/TEMPLATE](#) of the distribution while two examples of soil databases are in the directory [DATA/SOIL](#).

1.3.1 Table soils

soils is a registry table where each soil is defined by an alphanumeric *soil_code* linked to an integer *id_soil*. Typically this numeric field refers to a soil map shapefile in a geographical project and it is the id used to identify the computational unit in the **unit** database.

Table:  soils		
	id_soil	soil_code
	Filter	Filter
1	1	AGO1
2	2	AGOz
3	3	ARC1
4	4	ARC2

*example of **soils** table*

1.3.2 Table horizons

Each soil is typically composed of several pedological horizons, described in the **horizons** table, where each record describes the horizon in terms of pedological features such as texture, structure and organic matter content, that determine the shape of the soil water retention curve in the model.

In more details, each record of the **horizons** table contains:

- *soil_code*: unique alphanumeric code to identify the soil *
- *horizon_nr*: horizon number *
- *upper_depth*: horizon upper depth[cm] *
- *lower_depth*: horizon lower depth [cm] *
- *coarse_fragment*: percentage of soil particles > 2 mm [%]
- *organic_matter*: percentage of organic matter [%]

- *sand*: percentage of sand [%]
- *silt*: percentage of silt [%]
- *clay*: percentage of clay [%]
- *bulk_density*: bulk density [g cm^{-3}]
- *theta_sat*: water content at saturation [$\text{m}^3 \text{m}^{-3}$]
- *ksat*: water conductivity at saturation [cm day^{-1}]

*
*
*

* required data

soil_code	horizon_nr	upper_depth	lower_depth	coarse_fragment	organic_matter	sand	silt	clay	bulk_density	theta_sat	ksat
Filter	Filter	Filter	Filter	Filter	Filter	Filter	Filter	Filter	Filter	Filter	Filter
AGO1	1	0	60	0.0	32.4	0.66	0.25	0.09	0.6		
AGO1	2	60	80	0.0	8.6	0.23	0.49	0.28	0.8		
AGO1	3	80	110	0.0	2.0	0.44	0.46	0.1	1.42		
AGO1	4	110	150	0.0	0.8	0.83	0.13	0.04	1.76		
AGOz	1	0	50	0.0	11.96	0.426	0.334	0.24	0.7		
AGOz	2	50	65	0.0	6.08	0.252	0.35	0.398	0.9		
AGOz	3	65	74	0.0	24.35	0.722	0.198	0.08	0.7		
AGOz	4	74	85	0.0	10.42	0.668	0.262	0.07	0.8		
AGOz	5	85	150	0.0	2.46	0.778	0.149	0.073	1.76		
ARC1	1	0	50	10.0	1.2	0.189	0.414	0.397	1.35		
ARC1	2	50	75	0.0	0.1	0.189	0.417	0.394	1.4		
ARC1	3	75	150	0.0	0.1	0.116	0.48	0.404	1.45		
ARC2	1	0	50	10.0	1.2	0.189	0.414	0.397	1.35		
ARC2	2	50	75	0.0	0.1	0.189	0.417	0.394	1.4		
ARC2	3	75	150	0.0	0.1	0.116	0.48	0.404	1.45		

Example of *horizons* table

TODO describe **van genuchten**, **driessen** and **water retention** tables

1.4 db_crop

The *Crop* database is a SQLite file organized in two tables (**crop_class** and **crop**) containing crop classification and crop parameters.

A **crop_default.db** is available in the directory [DATA/TEMPLATE](#) and an example is in the test project [DATA/PROJECT/test/data](#).

1.4.1 Table crop_class

crop_class is a table where each crop classification (*id_class*) is linked to a prevalent crop (*id_crop*) described in the **crop** table.

Tabella: crop_class

	id_class	type	id_crop	irri_ratio
	Filtro	Filtro	Filtro	Filtro
1	SUMMER_HERBACEOUS	Summer herbaceous generic	CORN	0.6
2	FALLOW	Fallow (spontaneous natural growth)	FALLOW	0.0
3	KIWIFRUIT	Kiwifruit orchard	KIWIFRUIT	1.0
4	CORN	Corn	CORN	1.0
5	TOMATO	Tomato	TOMATO	1.0
6	PERENNIAL_HERBACEOUS	Perennial herbaceous generic	ALFALFA	0.0
7	WINTER_HERBACEOUS	Winter herbaceous generic	RAINFEDWHEAT	0.0
8	IRRI_WHEAT	Irrigated wheat	IRRIWHEAT	1.0
9	IRRI_ALFALFA	Irrigated Alfalfa	ALFALFA	1.0
10	PEAR	Pear orchard	PEAR	1.0
11	POTATO	Potato	POTATO	1.0
12	GRAPEVINE	Irrigated grapevine	GRAPEVINE	1.0
13	PEACH	Peach orchard	PEACH	1.0
14	SPARSE_FALLOW	Sparse fallow	SPARSEFALLOW	0.0

Example of *crop_class* table

The field *type* is a description of the crop class and the field *irri_ratio* [-] defines the irrigated percentage of the class. For instance, if in a study area ALFALFA is not irrigated the *irri_ratio* will be set to 0, whereas if it is irrigated or partially irrigated the *irri_ratio* will be set to a value between 0 and 1.

If the class *summer herbaceous* in the study area includes both irrigated and not irrigated crops, *irri_ratio* has to be set to the ratio between the two categories. For example *irri_ratio*=0.6 means that the irrigated area is 60% of the total area covered by summer herbaceous class.

Some crops (e.g. apple) are not yet simulated by CRITERIA, so they are not included in the **crop**. Here are two possible solutions for simulating a new crop:

- 1) the user can choose a crop that can be considered similar for development and water needs (e.g. pear could be used to simulate apple);
- 2) a new crop can be added in the **crop** table, following the instructions explained in the following paragraphs.

1.4.2 Table crop

Each crop is typically characterized by several parameters, described in the **crop** table, where each record describes the crop in terms of phenological characteristics, water needs and irrigation parameters.

In the table below, key parameters of the table (crop development, roots and irrigation water needs) are listed.

Crop development		
Parameter name	Description	Unit
plant_cycle_max_duration	Crop cycle max duration	days
thermal_threshold	Development thermal threshold	°C
degree_days_lai_increase	Degree days sum for LAI increase stage	°C
degree_days_lai_decrease	Degree days sum for LAI decrease stage	°C
lai_min	Minimum value of LAI	m ² m ⁻²
lai_max	Maximum value of LAI	m ² m ⁻²
lai_curve_factor_a	Factor <i>a</i> for LAI increase stage	[-]
lai_curve_factor_b	Factor <i>b</i> for LAI increase stage	[-]
kc_max	Crop coefficient (Kc) corresponding to the maximum LAI	[-]
Roots		
Parameter name	Description	Unit
root_depth_zero	Beginning depth of rooting system	m
root_depth_max	Maximum depth of rooting system	m
degree_days_root_increase	Degree days sum for the maximum development of the rooting system	°C
root_shape	Root shape factor (gamma function, cardioid, cylinder, ellipsoid)	[-]
psi_leaf	Leaf resistance	hPa

Water demand and irrigation		
Parameter name	Description	Unit
degree_days_start_irrigation	Degree days sum for the start of the irrigation period	°C
degree_days_end_irrigation	Degree days sum for the end of the irrigation period	°C
irrigation_shift	Minimum number of days since the last irrigation	days
irrigation_volume	Crop irrigation volume	mm/day
stress_tolerance	Threshold of Tr/Tmax ratio (actual transpiration/maximum transpiration) above which stress is tolerated 0 = any water stress is tolerated 1 = no water stress is tolerated	[-]
raw_fraction	Fraction of readily available water	[-]
max_height_surface_puddle	Maximum height of the surface puddle (i.e. amount of water that surface can retain without runoff)	mm

Parameters in the **crop** table

1.4.3 Crop parameters description

To define the crop cycle, key parameters to set are *sowing_doy* (the day of the year in which usually the crop is seeded) and *plant_cycle_max_duration* (the maximum length of the crop cycle in days). The computation of the phenological stages is carried out on the basis of the thermal threshold that the user must define in the *thermal_threshold* field.

The degree days sum needed by the crop for the emergence (*degree_days_emergence*), for the maximum leaf area index development (*degree_days_lai_increase*) and for the leaf area index senescence (*degree_days_lai_decrease*) must be set.

upper_thermal_threshold field defines the maximum cardinal temperature, which is the maximum temperature value at which the crop could develop.

The leaf area index development is simulated by using the following parameters: minimum leaf area index at the beginning of the crop cycle (*lai_min*), maximum leaf area index

reached during the season (*lai_max*) and, especially for fruit trees with a grass cover, leaf area index of the grass (*lai_grass*).

The maximum crop coefficient (*kc_max*) is used to compute actual evapotranspiration.

The crop rooting system development is simulated by using the following parameters: depth of the beginning of roots with respect to the ground (*root_depth_zero*) e.g. the depth of the root collar, the maximum depth of the roots (*root_depth_max*), the degree days sum for the full development of the rooting system (*degree_days_root_increase*) and the shape of the roots (*root_shape*). Currently, three shape factors codes are considered:

- 1 → cylinder
- 4 → cardioid
- 5 → gamma distribution

In addition, a coefficient of deformation (*root_shape_deformation*), expressed as a value ranging from 0 to 2, can be used to adapt the selected shape to the actual shape of the crop (only for cylinder and cardioid, it does not affect the gamma distribution).

The *max_height_surface_puddle* is the amount of water that surface can retain without runoff, typically a few millimeters of water, except for some crops (such as rice) where the surface is shaped specifically to retain water. This parameter can be increased if the field is worked (the clods retain water) or decreased if the field is not flat and allows rapid runoff (for example on hills).

In order to assess the crop water demand, the irrigation process is controlled by the parameters listed in the table: *irrigation_shift* (the number of days between two irrigations) and *irrigation_volume* (the maximum volume of water distributed for each irrigation during the crop cycle in mm). These parameters allow the user to define the irrigation methods (i.e. micro irrigation, sprinkler irrigation) depending on time shifts and maximum volumes for each irrigation.

The irrigation season length is controlled by *degree_days_start_irrigation* and *degree_days_end_irrigation* parameters: the actual irrigation period starts and stops according to a degree days sum, taking into account the weather conditions of every specific year, anticipating it in warm years and delaying it in cold ones.

The water stress sensitivity specific for the crop is expressed by the *raw_fraction*, i.e. the fraction of readily available water between the wilting point and the field capacity.

Another parameter useful to calibrate the irrigation needs for the crop is *stress_tolerance*: it expresses the tolerance of the crop to water stress as the ratio between actual transpiration and maximum transpiration, where 0 means that any water stress is tolerated and 1 that no water stress is tolerated by the crop.

1.5 db_unit

The Unit database contains one table (**units**) that lists the project computational units and the model specific options for each unit. A computational unit (*ID_CASE*) is a unique combination of one crop (*ID_CROP*), one meteo (*ID_METEO*) and one soil (*ID_SOIL*).

WARNING: *ID_CROP* in the table **units** must correspond to the *id_class* of the **crop_class** table in the crop database. (TODO fix inconsistency).

A **template_units.db** is available in the directory [DATA/TEMPLATE](#) and an example is in the test project [DATA/PROJECT/test/data](#)

units	
ID_CASE	TEXT
ID_CROP	TEXT
ID_METEO	TEXT
ID_SOIL	NUMERIC
hectares	NUMERIC
numerical_solution	INTEGER
use_water_table	INTEGER
water_retention_fitting	INTEGER
optimal_irrigation	INTEGER
slope	REAL

*Structure of the **units** table*

Several model parameters for each computational unit can be defined:

- *hectares* [ha] of the unit, used only in geographical version of the model;
- *numerical_solution*: (1: true, 0: false, default: 0) if true, use the soil water flux numerical algorithm, otherwise a simplified conceptual algorithm;
- *use_water_table*: (1: true, 0: false, default: 1) if true, the model computes the capillary rise from water table; in case of lack of water table data a condition of free drainage at the bottom of the soil will be simulated;
- *water_retention_fitting*: (1: true, 0: false, default: 1) if true, the soil parameters will be fitted using data in **water_retention** table, if available;
- *optimal_irrigation*: (1: true, 0: false, default: 0) if true, use ideal subirrigation to restore field capacity in the root zone without losses;
- *slope*: [-] slope of the unit, used only in the numerical solution to compute the flow in the lateral boundaries.

ID_CASE	ID_CROP	ID_METEO	ID_SOIL	numerical_solutio	use_water_table	water_retention_fittin	stimal_irrigati	slope
Filtro	Filtro	Filtro	Filtro	Filtro	Filtro	Filtro	Filtro	Filtro
PEAR	PEAR	ERG5_01015...	267	0	1	0	0	0.01
PEAR numerical	PEAR	ERG5_01015...	267	1	1	0	0	0.01
PEAR numerical no ...	PEAR	ERG5_01015...	267	1	0	0	0	0.01
KIWI	KIWIFRUIT	ZATTAGLIA	97	0	0	0	0	0.02
KIWI numerical	KIWIFRUIT	ZATTAGLIA	97	1	0	0	0	0.02
RAVONE	SPARSE_FALLOW	ERG5_01422	104	0	0	0	0	0.04
RAVONE numerical	SPARSE_FALLOW	ERG5_01422	104	1	0	0	0	0.04
POTATO	POTATO	ERG5_01015	268	0	0	0	0	0.01
POTATO numerical	POTATO	ERG5_01015	268	1	1	0	0	0.01

Example of the **units** table

1.6 db_output

Model output is stored in a multi-table database, one table is created for each case in the **units** table, naming it with the corresponding ID_CASE.

Default output variables that Criteria-1D automatically saves are listed in the following table:

DATE	date (yyyy-mm-dd)
PREC	Precipitation [mm]
IRRIGATION	Irrigation water needs [mm]
WATER_CONTENT	Soil water content in the first meter [mm]
SURFACE_WC	Surface water content [mm]
AVAILABLE_WATER	Available water (water content - wilting point) in the first meter [mm]
FRACTION_AW	Fraction of available water with respect to AWC (field capacity - wilting point) in the first meter [mm]
READILY_AW	Readily available water in the rooting zone [mm]
RUNOFF	Surface runoff [mm]
DRAINAGE	Soil deep drainage [mm]
LATERAL_DRAINAGE	Soil lateral drainage [mm]
CAPILLARY_RISE	Capillary rise from watertable [mm]
ETO	Reference evapotranspiration [mm]
TRANSP_MAX	Maximum crop transpiration [mm]
TRANSP	Actual crop transpiration [mm]
EVAP_MAX	Maximum evaporation [mm]
EVAP	Actual evaporation [mm]
LAI	Leaf area index [m ² m ⁻²]
ROOT_DEPTH	Root depth [m]

BALANCE	Water balance error (for numerical solution) [mm]
---------	---

Additional output and specific computation depth can be added by user, defining it in the project.ini file. The possibly additional output are:

waterContent	Volumetric water content at specific depth [m ³ m ⁻³]
waterPotential	Water potential at specific depth [kPa]
waterDeficit	Sum of water deficit (FC - water content) from zero to user defined depth [mm]
awc	Sum of Available Water Capacity (FC-WP) from zero to user defined depth [mm]

The calculation depth can be set in the project.ini as a depth list in [cm]. The following example saves the water content and water potential at 15, 30 and 50 centimeters depths and the sum of the water deficit in the first meter of soil:


```
[output]
waterContent=15,30,50
waterPotential=15,30,50
waterDeficit=100
```

The corresponding fields in the db output will be named:

```
SWC_15, SWC_30, SWC_50
WP_15, WP_30, WP_50
DEFICIT_100
```

2. ALGORITHMS

The Soil Water Balance (SWB) is the result of interactions of all the hydrological processes occurring between soil, vegetation and atmosphere.



SWB conceptual scheme

The amount of water from rain or irrigation that infiltrates into the ground depends on surface conditions, on the hydrological characteristics of the first layer of soil and its water content. The water that could not infiltrate into the soil is collected in puddles formed by surface roughness. Once puddles are filled, surface runoff occurs.

The processes of storage and infiltration are governed by soil water potential differences. Each soil horizon is characterized by its water retention curve. Depending on the water content, the layer can hold water or transfer it to the layer below. In the presence of a water table, there may also be a supply of water to the soil deeper layers because of capillary rise.

The presence of a crop produces water loss in the root zone through root absorption, and simultaneously reduces evaporation loss in the surface layers. Depending on the type of soil, its water content and the phenological stage of the crop, the water in the soil is more or less available to plants, thus affecting its transpiration rate.

Once the crop parameters are properly set, it is possible by means of the SWB to estimate the crop water needs not fulfilled by the soil water content that have to be provided by irrigations.

CRITERIA-1D model follows the approach of Driessen (1986), Driessen and Konijn (1992) but it assumes a multilayered soil and explicitly computes approximate values of daily actual evaporation and transpiration, water flows between layers, deep drainage, surface and subsurface runoff and capillary rise. The software is written in C++ language with use of Qt libraries, thus it can be compiled on several platforms.

2.1 Water

In a soil water balance model the following concepts play a key role:

- Field Capacity (FC): the presumed water content at which internal drainage ceases;
- Wilting Point (WP): the minimal water content below which the plant is not able to withdraw water;
- Soil texture classification: soil is classified by the fractions of specific ranges of particle sizes (typically sand, silt, and clay). Classifications are named for the primary constituent particle size or a combination of the most abundant particles sizes, e.g. "sandy clay"; the generic term "loam" is used to describe a roughly equal concentration of sand, silt, and clay;
- Infiltration: is the process of transferring water from the soil surface into the soil, where it becomes *soil water content* and originates redistribution processes such as *subsurface flow* in the unsaturated zone and *groundwater flow* in the saturated zone;
- Conceptual models: approximation of the physical processes through simplified schemes adapted to describe reality by means of semi-empirical models.

2.1.1 Water retention curve

The soil water retention in the model is described by the van Genuchten equation (van Genuchten, 1980), modified by Ippish *et al.* (2006). The original van Genuchten equation is:

$$\theta(h) = \theta_r + (\theta_s - \theta_r) \left(\frac{1}{[1 + (\alpha h)^n]^m} \right)$$

where $\theta(h)$ is the volumetric water content at the water potential h , θ_s and θ_r are the saturated and residual water contents, α is the coordinate of the inflexion point of the retention curve, m and n are dimensionless factors related to the pore-size distribution.

We used the typical restriction $m = 1 - 1/n$

The hydraulic conductivity is calculated by the equation of Mualem (1976):

$$K(h) = \frac{K_s (1 - (\alpha h)^{mn} [1 + (\alpha h)^n]^{-m})^2}{[1 + (\alpha h)^n]^{ml}}$$

where K_s is the saturated hydraulic conductivity, and l is an empirical parameter that accounts for pore tortuosity.

Ippisch *et al.* (2006) pointed out that the van Genuchten-Mualem model, under certain conditions, is problematic when water retention data are used to predict the hydraulic conductivities and they demonstrated that if $n < 2$ or $\alpha h_e > 1$ (where h_e is the air-entry value of the soil, corresponding to the largest pore radius), the van Genuchten-Mualem predicts erroneous hydraulic conductivities. In these cases, an explicit air-entry value h_e has to be included, leading to a modified van Genuchten-Mualem model:

$$S_e = \begin{cases} \frac{1}{S_c} [1 + (\alpha h)^n]^{-m} & \text{if } (h > h_e) \\ 1 & \text{if } (h \leq h_e) \end{cases}$$

where S_e is the degree of saturation and $S_c = [1 + (\alpha h_e)^n]^{-m}$ is the water saturation at the air-entry potential h_e .

The resulting hydraulic conductivity using the Mualem model is:

$$K = \begin{cases} K_s S_e^l \left[\frac{1 - (1 - (S_e S_c)^{1/m})^m}{1 - (1 - S_c^{1/m})^m} \right]^2 & \text{if } (S_e < 1) \\ K_s & \text{if } (S_e \geq 1) \end{cases}$$

where l is the same parameter as in the original Mualem equation.

The following table lists the parameters used in the model for the USDA texture classification.

texture	alpha	n	he	theta_r	theta_s	k_sat	l
Filter	Filter	Filter	Filter	Filter	Filter	Filter	Filter
sand	0.39	1.7	0.07	0.01	0.38	192.0	0.5
loamy sand	0.35	1.5	0.1	0.02	0.39	96.0	0.5
sandy loam	0.29	1.4	0.15	0.02	0.4	48.0	0.5
silt loam	0.13	1.2	0.26	0.03	0.44	9.6	0.5
loam	0.17	1.21	0.23	0.03	0.42	12.0	0.5
silt	0.1	1.24	0.27	0.03	0.44	2.4	0.5
sandy clayloam	0.22	1.22	0.2	0.03	0.41	12.0	0.5
silty clayloam	0.13	1.2	0.31	0.03	0.46	2.4	0.5
clayloam	0.18	1.18	0.27	0.04	0.45	4.8	0.5
sandy clay	0.21	1.18	0.25	0.04	0.44	3.6	0.5
silty clay	0.17	1.16	0.33	0.05	0.48	1.2	0.5
clay	0.16	1.16	0.33	0.05	0.48	0.8	0.5

Soil parameters for USDA texture classes

The values of the table were produced by a comparison of data presented in several papers on this subject (Wösten et al., 1998; Simota and Mayr, 1996; Carsel and Parrish, 1988; Schaap, Leji and van Geuchten, 2001).

2.2 Water flow numerical model

TODO

Numerical solution of water flow is detailed at the [following](#) web page(section 1.1.2)

2.3 Layer-based empirical model

Conceptual models approximate the physical processes through simplified schemes adapted to describe reality by means of semi-empirical models. While conceptual models are not able to describe the processes with the same precision of physically-based models, they present the following advantages: a higher computational speed, which facilitates their use in applications designed for simulations at larger scales; lower need of parameters and input data, which could be required in case of more complex models.

The following paragraphs will describe all the components of the layer-based empirical model implemented in CRITERIA.

2.3.1 Maximum infiltration

The amount of water that can flow through the layer depends on its water content and the permeability of the same and is estimated using the following equation (Driessen, 1986):

$$I_{max} = 10[S_0(1 - \theta/\theta_{sat}) + A]$$

Where:

I_{max}	maximum infiltration	[mm d ⁻¹]
S_0	standard sorptivity	[cm d ⁻¹]
θ	volumetric water content of the layer	[m ³ m ⁻³]
θ_{sat}	volumetric water content at saturation	[m ³ m ⁻³]
A	hydraulic conductivity at the wetting front	[cm d ⁻¹]


The sorptivity represents the infiltration rate determined by the single matric potential, the standard sorptivity S_0 being defined for a completely dry soil. Reference values for these parameters, depending on the different soil textural classes, are reported in the following table:

Textural classes	A [cm d-1]	S_0 [cm d-1]	K_0 [cm d-1]
Sand (S)	30.33	21.44	50
Sandy Loam (SL)	17.80	19.20	26.5
Loamy Sand (LS)	9.36	17.57	12
Silt Loam (SiL)	5.32	14.46	6.5
Loam (L)	3.97	11.73	5
Silt (Si)	8.88	13.05	14.5
Sandy Clay Loam (SCL)	16.51	19.05	23.5
Silty Clay Loam (SiCL)	1.18	6.15	1.5
Clay Loam (CL)	0.76	4.70	0.98
Sandy Clay (SC)	2.94	10.74	3.5
Silty Clay (SiC)	0.80	3.98	1.3
Clay (C)	0.15	1.93	0.5

Reference values of infiltration speed of the wetting front (A), of the standard sorptivity (S_0) and the saturated conductivity (K_0) depending on the different textural classes (Driessen, 1986).

The absolute values of I_{max} vary by several orders of magnitude as a function of textural class: in particular, maximum infiltration is greatly reduced in both dry and wet conditions by

increasing the clay content. The following figure shows the effect of soil moisture on I_{max} values.



Maximum daily infiltration (I_{max}) after a rain at field capacity and wilting point for different soil textures (S=Sand, Si=Silt, C=Clay, L=Loam).

2.3.2 Infiltration and redistribution

The soil profile is divided by the model into a number of thin computational layers (usually 2 cm of thickness), and the computation of water flow by layer starts from the bottom of the profile, depending on soil maximum depth.

A wetting front is determined when a layer has water content greater than its field capacity (FC), and an initial flow is defined considering the amount of water that can be moved and by the difference between the actual water content and the field capacity. The amount of water that actually moves and the length of the downward shift depends on the water content and the texture of the underlying layers.

Each layer is characterized by an infiltration of the maximum daily amount (I_{max}). To estimate the maximum displacement of the waterfront, the maximum infiltration of the underlying layer at the waterfront is calculated. If the water content of the layer exceeds the field capacity, the amount in excess is transferred to the next one. This computation continues until the waterfront encounters a layer in which the amount of incoming water determines a total water content that is lower than FC, then the waterfront is stopped.


Two conditions have to be satisfied:

1. the sum of the flows passed through a layer cannot exceed its maximum daily infiltration;

2. in case the waterfront meets a saturated layer, the front stops at the layer above the saturated layer.

The first condition limits the passage of water in case of clay layers with low maximum daily infiltration: in this case it forms a suspended water table.

The second condition simulates the slowing down of the waterfront when it approaches a saturation condition: the waterfront that is arriving lays on the previous one.



Infiltration into the soil profile of moisture fronts A, B, C and D

In the figure above, the infiltration of several wetting fronts in different conditions of permeability is shown:

- the front A, crossing through medium permeable layers, moves downwards while remaining separate from the other fronts;
- the front B crosses the same permeable layers and merges with front C, whose infiltration is slowed by the presence of a less permeable layer;
- the rain partially infiltrates creating a new front D;
- The water in excess with respect to surface I_{max} creates a puddle on the ground.

In cases where the free water reaches the last layer, it leaves the system as deep drainage.

2.3.3 Surface and subsurface runoff

The agricultural fields are usually delimited by drains and ditches, therefore surface and sub-surface runoff can be assumed as outflow from the system through these means.

The surface runoff occurs when the soil surface roughness cannot hold puddle water. The process is simulated considering the maximum height of storage surface, which depends on:

- crop species; for instance *Oryza sativa* (rice) has typically a higher puddle than other cereals.
- crop type, i.e. annual and perennial. Annual crops are typically herbaceous crops that need tillages and thus a default value of 5-10 mm of clod height is simulated. For perennial crops (trees) usually tillages are not performed.

Maximum sub-surface runoff is estimated by the following equation, which solves the universal flow equation as a function of distance and radius of drains (Driessen, 1986):

$$D_{max} = 10 \cdot k_0 \cdot \psi / (\psi + L_d / \pi \cdot \ln(L_d / r_d \pi))$$

where:

D_{max} is maximum subsurface runoff (lateral drainage) [mm]

k_0 is saturated hydraulic conductivity (see table in maximum infiltration paragraph) [cm/day]

ψ is hydraulic head midway between drains [m]

L_d is drain spacing [m]; default: 100 m

r_d is drain radius [m] default: 0.25 m

2.3.4 Capillary rise

Capillary rise is computed by the steady state solution of Darcy's equation.

The vertical water flow between two arbitrary points follows Darcy's law:

$$F = k_h \cdot dH/dL$$

where:

F is the flow rate (cm d⁻¹)

dH is the difference in hydraulic head (cm)

dL is the distance of flow (cm)

k_h is the hydraulic conductivity at matric suction h (cm d⁻¹)

The total hydraulic head H is composed of both gravity forces and matric suction:

$$H = h + g$$

Where h is the matric suction and g the gravity head, equal to the vertical distance (cm) between soil layer and the groundwater level.

The total hydraulic head H is positive if the matric suction h exceeds the vertical distance between the layer and the groundwater. A positive hydraulic head allows positive water flow from the groundwater to the point with matric suction h . This water flow is called capillary rise.

Therefore capillary rise can be computed by the steady state solution of Darcy's equation as:

$$CR = k_h \cdot (dh/dz - 1)$$

Where:

CR is the capillary rise (cm d⁻¹)

h is the matric suction (cm)

z is the distance between the soil layer and the groundwater level.

2.4 Crop

Crop development in the SWB model is computed by means of daily minimum and maximum temperature, driving the leaf area index (LAI) curve in three stages: emergence, increase and senescence (LAI decrease). In addition, the root development is driven by temperatures and the root density follows three main root shapes: cylinder, cardioid and gamma distribution.

LAI drives the partitioning of the evapotranspiration in potential evaporation and transpiration. Potential evaporation is assigned to the surface layer (if it is wet) and to the first soil layers (up to 15 cm), while potential transpiration is assigned to the rooting system, subdivided depending on the root density.

The actual evaporation and transpiration can be lower than the potential, depending on the actual soil water content and on the crop physiological parameters.

TODO

Crop processes are detailed at the [following](#) web page

2.4.1 Potential evapotranspiration

The term evapotranspiration refers to the total water that is moved from the soil to the atmosphere by evaporation from surface and soil and by transpiration from plants.

The evapotranspiration rate increases until water is available. The limit is called the *maximum evapotranspiration* (ET_m) and is defined as the amount of water evapotranspired per unit time from a uniform crop that has full water availability.

The *reference evapotranspiration* (ET_0) is the amount of water evapotranspired from a reference crop (*Festuca arundinacea* Schreb., multispecies grass) maintained between 8 and 15 cm height, completely covering the ground with plenty of water availability. ET_0 represent the water demand by the atmosphere, and it depends on atmospheric and surface conditions (temperature, solar radiation, wind speed, air water content, leaf water content).

The ET_0 estimation methods proposed in literature are many, characterized by different input variables and made for different time scales integration. In CRITERIA-1D, **Hargreaves and Samani equation** (1985) is used to calculate daily reference evapotranspiration.

The Hargreaves method needs only latitude of the computation area and daily maximum and minimum temperature for the estimation:

$$ET_0 = 0.0023 \cdot \frac{Rad_{ext}}{2.456} \cdot (T_{avg} + 17.78) \cdot (T_{max} - T_{min})^{0.5}$$

Where:

ET_0 is reference evapotranspiration [mm d^{-1}];

Rad_{ext} is extraterrestrial radiation [$\text{MJ m}^{-2} \text{d}^{-1}$];

T_{max} and T_{min} are daily maximum and minimum temperature of the air [$^{\circ}\text{C}$];

T_{avg} is the daily average temperature, computed as $T_{avg} = (T_{max} + T_{min})/2$

Rad_{ext} is the potential radiation that would reach Earth's surface in the absence of the atmosphere and it can be computed by:

$$Rad_{ext} = 24 \cdot 4.921 \cdot d_r \cdot \pi \cdot (\Omega \sin(lat) \cdot \sin(\delta) + \cos(lat) \cdot \cos(\delta) \cdot \sin(\Omega))$$

where:

4.921 is the hourly solar constant [$\text{MJ m}^{-2} \text{h}^{-1}$];

lat is the latitude of the computation area [rad];

doy is the day of the year;

d_r is the inverse Earth-Sun relative distance, compute by:

$$d_r = 1 + 0.033 \cdot \cos(2 \cdot \pi \cdot doy / 365)$$

Ω is the sunset hour angle [rad] computed by:

$$\Omega = \arccos(-\tan(lat) * \tan(\delta))$$

Finally δ is the solar declination [rad], computed by:

$$\delta = 0.4093 \cdot \sin((2\pi/365) \cdot doy - 1.39)$$

2.5 Irrigation

Every crop has its own sensitivity to water stress, defined by the ability to use the water present in the portion of soil explored by the rooting system. This value is defined by the fraction of readily available water by the root.

The amount of water that can be easily available in the root profile is calculated using this function, which integrates the height of water that can be easily used on the layer of ground affected by the roots:

$$H_2O_{available} = \sum_{l=iniRootDepth}^{rootDepth} (WC_l - (FC_l - fRAW * (FC_l - WP_l)))$$

where:

$H_2O_{available}$ is the easily available water content [mm]

$fRAW$ is the fraction of readily available water [-]

WC_i , FC_i and WP_i are the water content, field capacity and wilting point of the layer [mm]

The easily available water is used to assess when to irrigate the crop: the model defines the irrigation time when $H_2O_{available}$ is below zero.

In more detail, an irrigation is performed in the model if all the following conditions are fulfilled:

1. the current day of simulation is included in the irrigation season;
2. the number of days since the last irrigation is higher than the irrigation shift;
3. the forecast rain is lower than 5 mm;
4. the ratio between actual and potential transpiration is lower than the tolerated stress percentage for the crop;
5. the easily available water is lower than zero.

The irrigation amount is computed as the minimum value among the predefined irrigation quantity for the crop and the maximum quantity of water that can infiltrate daily without runoff.

CRITERIA references

2021. De Faria, B. T., Aguzzi, C., Bates, T., Campbell, C., Tomei, F., Bittelli, M., & Roffia, L. (2021, November). Predict soil moisture into the future: on the integration of CRITERIA-1D into ZENTRA cloud. In 2021 IEEE International Workshop on Metrology for Agriculture and Forestry (MetroAgriFor) (pp. 331-335). IEEE.

2021. Villani, G., Tomei, F., Pavan, V., Pirola, A., Spisni, A., & Marletto, V.. The iCOLT climate service: Seasonal predictions of irrigation for Emilia-Romagna, Italy. *Meteorological Applications*, 28(4), e2007.

2020. Suci, N., et al. Evaluation of groundwater contamination sources by plant protection products in hilly vineyards of Northern Italy. *Science of The Total Environment*, 141495.

2020. Ricchi, T., Alagna, V., Villani, G., Tomei, F., Toscano, A., & Baroni, G. Sensitivity of the agro-hydrological model CRITERIA-1D to the Leaf Area Index parameter. In 2020 IEEE International Workshop on Metrology for Agriculture and Forestry (MetroAgriFor) (pp. 247-251).

2020. Martini, E., Wollschläger, U., Bittelli, M., Tomei, F., Werban, U., Zacharias, S., & Roth, K. Process-based hydrological modeling: accounting for subsurface heterogeneity by integrating pedology, geophysics and soil hydrology. In EGU General Assembly Conference Abstracts (p. 9894).

2020. Chitu, Z., Tomei, F., Villani, G., Di Felice, A., Zampelli, G., Paltineanu, I. C., ... & Costache, R. Improving Irrigation Scheduling Using MOSES Short-Term Irrigation Forecasts and In Situ Water Resources Measurements on Alluvial Soils of Lower Danube Floodplain, Romania. *Water*, 12(2), 520.

2019. Villani, G., Nanni, S., Tomei, F., Pasetti, S., Mangiaracina, R., Agnetti, A., ... & Castellari, S. The RainBO Platform for Enhancing Urban Resilience to Floods: An Efficient Tool for Planning and Emergency Phases. *Climate*, 7(12), 145.

2018. Villani, G., et al. Soil Water Balance Model CRITERIA-ID in SWAMP Project: Proof of Concept. 23rd Conference of Open Innovations Association (FRUCT) (pp. 398-404). IEEE.

2018. Strati, V., Albéri, M., Anconelli, S., Baldoncini, M., Bittelli, M., Bottardi, C., Solimando, D., Tomei, F., Villani, G., & Mantovani, F. Modelling soil water content in a tomato field: proximal gamma ray spectroscopy and soil–crop system models. *Agriculture*, 8(4), 60.

2017. Chitu, Z., Villani, G., Tomei, F., Minciuna, M., Aldea, A., Dumitrescu, A., ... & Neagu, D. Water balance analysis for efficient water allocation in agriculture. A case study: Balta Brailei, Romania. EGUGA, 18943.
2016. Consoli, S., Licciardello, F., Vanella, D., Pasotti, L., Villani, G., & Tomei, F. Testing the water balance model criteria using TDR measurements, micrometeorological data and satellite-based information. *Agricultural Water Management*, 170, 68-80.
2015. Campi, P., Modugno, F., Navarro, A., Tomei, F., Villani, G., & Mastrorilli, M. Evapotranspiration simulated by CRITERIA and AquaCrop models in stony soils. *Italian Journal of Agronomy*, 10(2), 67-73.
2015. Bittelli, M., Campbell, G. S., Tomei, F. *Soil Physics with Python, Transport in the Soil-Plant-Atmosphere System*. Oxford University Press, 464 pages, ISBN: 978-0-19-968309-3.
2014. Dottori, F., Grazzini, F., Di Lorenzo, M., Spisni, A., & Tomei, F. Analysis of flash flood scenarios in an urbanized catchment using a two-dimensional hydraulic model. *Proceedings of the International Association of Hydrological Sciences*, 364, 198-203.
2014. Villani G., Botarelli L., Marletto V., Spisni A., Pavan V., Pratizzoli W. & Tomei F. iCOLT – Seasonal forecasts of crop irrigation needs at ARPA-SIMC. *ECMWF Newsletter*, 138: 30-33.
2014. Campi, P., Modugno, F., Mastrorilli, M., Tomei, F., Villani, G., & Marletto. Evapotranspiration of tomato simulated with the CRITERIA model. *Italian Journal of Agronomy*, 93-98.
2011. Bittelli M., Pistocchi A., Tomei F., Roggero P.P., Orsini R., Toderi M., Antolini G. and Flury M. CRITERIA-3D: A Mechanistic Model for Surface and Subsurface Hydrology for Small Catchments. In: *Soil Hydrology, Land Use and Agriculture: Measurement and Modelling*. M. Shukla Ed. 416 pp.
2011. Villani G., Tomei F., Tomozeiu R., Marletto V. Climate scenarios and their impacts on irrigated agriculture in Emilia-Romagna, Italy. *Italian J. Agrometeorol.*, 16.
2010. Bittelli M., Tomei F., Pistocchi A., Flury M., Boll J., Brooks E.S., Antolini G. Development and testing of a physically based, three-dimensional model of surface and subsurface hydrology. *Adv. Wat. Resour.*, 33, 106-122.
2009. Antolini G., Bertacchini A., Carnevali G., Dal Re L., Laruccia N., Marletto V., Missiroli A., Ponzoni G., Quartieri M., Scotti C., Selmi C., Tabaglio V., Tagliavini M. Regional scale validation of two soil water and nitrogen models on wheat (*Triticum aestivum* L.) and peach (*Prunus persica* L.). *Proc. 16th Nitrogen Workshop*, June 28 - July 1 Torino

2007. Marletto V., Ventura F., Fontana G., Tomei F. Wheat growth simulation and yield prediction with seasonal forecasts and a numerical model. *Agric. For. Meteorol.* 147:71-79.
2007. Tomei F., Antolini G., Bittelli M., Marletto V., Pasquali A., Van Soetendael M. 1. Validazione del modello di bilancio idrico Criteria. *AIAM 2007, Quaderno riassunti*, 66-67.
2007. Rinaldo S., Carollo F., Leoni C., Marletto V., Tonelli T., Bonaiti G. Water requirements calculation for crops irrigated with the Adige river water. *ICID 22nd European Regional Conference 2007, 2-7 September 2007 - Pavia*
2006. Marletto V.. CRITERIA: ecco il modello regionale di bilancio idrico. *Agricoltura* 34(6): 127-128
2006. Carollo F., Rinaldo S., Marletto V., Tonelli T., Bonaiti G. Monitoraggio e calcolo del fabbisogno idrico di singole colture agrarie. *Atti ASITA 2006*.
2006. Tomei F., Fontana G. Studio di validazione del modello CRITeRIA nella descrizione del trasporto dei nitrati. *Convenzione Assessorato Agricoltura*.
2006. Fontana G., Ventura F., Tomei F., Tonelli T., Marletto V. Modelli agrometeorologici e previsioni stagionali per la stima delle rese agricole. *Atti Aiam 2006*.
2005. Marletto V., Zinoni F., Botarelli L., Alessandrini C. Studio dei fenomeni siccitosi in Emilia-Romagna con il modello di bilancio idrico Criteria (extended abstract). *RIAM 9*: 32-33. *Quaderno dei riassunti Convegno AIAM Vasto/Caramanico 3-5/5/2005*.
2005. Marletto V., Zinoni F., Crisculo L., Fontana G., Marchesi S., Morgillo A., Van Soetendael M., Ceotto E., Andersen U. Evaluation of downscaled DEMETER multi-model ensemble seasonal hindcasts in a northern Italy location by means of a model of wheat growth and soil water balance. *Tellus A*, 57(3), 488-497.
2004. Zinoni F., Tonelli T., Marletto V. Studio dell'effetto della tecnica agronomica sul rilascio di nutrienti (azoto) in falda nella pianura piacentina. Appendice: descrizione del modello Criteria. In: *Progetto AQUANET, Rapporto finale, Provincia di Piacenza*, 93-115.
2004. Zinoni F., Alessandrini C., Marletto V. Bilancio idrico dei suoli agricoli. Applicazione del modello CRITERIA per la stima dei consumi idrici e delle irrigazioni relative ai principali ordinamenti colturali, nonché dei flussi idrici superficiali e profondi. *Studio ambientale sul comprensorio ceramico*.

2004. Pistocchi A., Tomei F. Analisi numerica dei processi idrologici nel suolo agrario: integrazione del modello CRITERIA con un modello di bilancio idrologico fisicamente basato. Approfondimenti. Relazione tecnica finale progetto CLIMAGRI, 38 pp.

2003. Zinoni F., Tonelli T. Studio del rilascio di azoto di origine agricola nei suoli del comune di Castelfranco Emilia utilizzando il modello CRITERIA.

2003. Pistocchi A., Tomei F. Un modello accoppiato 3D di runoff e deflusso nel mezzo poroso nel quadro del sistema di supporto alle decisioni Criteria. Atti AIAM 2003, 285-296.

2002. Zinoni F., Marletto V., Tiberi M., Accorsi C., Roggero P.P., Toderi M. CRITERIA: prime valutazioni per l'applicazione del modello nelle Marche. Relazione tecnica. Nota Interna ASSAM, Agenzia Sviluppo Agricolo Marche.

2002. Zinoni F., Bardasi G., Battilani A., Ducco G., Marletto V., Van Soetendael M., Tonelli T. Studio del carico di inquinanti di origine agricola: applicazione del modello CRITERIA a un comprensorio della bassa bolognese.

2001. Marletto V., Criscuolo L., Van Soetendael M. Implementation of Wofost in the framework of the Criteria geographical tool. Proc. of the 2nd Int. Symp. Modeling Cropping Systems, European Society for Agronomy, Florence, 16-18 July 2001, 219-220.

2001. Marletto V., Zinoni F. Messa a punto del modello CRITERIA per la valutazione del trasporto di nutrienti. Atti del seminario "Iniziative per contenere il fenomeno dell'eutrofizzazione nel Mare Adriatico" promosso da Direzione Generale Agricoltura - Direzione Generale Ambiente - ARPA Regione Emilia Romagna, Bologna, giovedì 7 Ottobre 1999, 114-120.

2001. Zinoni F., Ducco G., Marletto V., Van Soetendael M. Uso del modello CRITERIA per la valutazione del rischio di inquinamento azotato dei corpi idrici. Modellistica e qualità ambientale. ANPA RTI CTN_SSC 1/2001, 67-77. Anche in Atti di GEOFLUID 2000, Piacenza, 5 ottobre 2000, a cura di Elisabetta Russo.

2000. Ducco G. Completamento ed attivazione delle procedure per la simulazione del bilancio dell'azoto in CRITERIA. Relazione conclusiva. Nota interna SMR, 51 pp.

1999. Zinoni F., Marletto V. CRITERIA: bilancio idrico e GIS per la prevenzione dell'impatto ambientale di origine agricola. Agricoltura Ricerca n. 180/181 p: 102-109

1999. Zinoni F., Sarno G. Sviluppo, calibrazione e validazione del programma CRITERIA. Relazione finale, Feb. 1999. Piano Trien. per la Tutela amb. 1994-1996. Sch. Int. N.23-24. Messa a punto di un modello previs. rel. al bil. idrico di tipologie di suolo rinvenibili princip. in aree di conoide e interconoide tra i fiumi Secchia e Panaro.

1998. Zinoni F., Marletto V., Ducco G. CRITERIA - un sistema per la gestione territoriale del bilancio idrico. Atti Seminario AIAM '98, Firenze 2 aprile 1998: 67-74.

1998. Marletto V., Zinoni F., Tonelli T., Ducco G. CRITERIA: a Geographical Soil Water Balance Modeling Tool for Environmental Applications at the Regional Scale. Convegno 7th ICCTA International Congress for Computer Technology in Agriculture. Firenze 15-18 Novembre 1998, p. 43.

1998. Marletto V., Zinoni F. The Criteria project: integration of satellite, radar, and traditional agro climatic data in a GIS-supported water balance modeling environment. In: EUR 18328, Dalezios N.R. (ed.), 1998. Proc. COST 77, 79, 711 Int. Symp. on Applied Agrometeorology and Agroclimatology, Volos, Grecia, 24-26 april 1996, ISBN 92-828-4137-5, 173-178.

1998. Zinoni F., Marletto V. CRITERIA: progetto per ridurre l'impatto ambientale di origine agricola. Rivista ARPA, Luglio-Agosto 1998

1996. Zinoni F., Marletto V., Libè A., Raggi C., Tonelli T., Trevisan M., Capri E. Pesticide transport simulated within the CRITERIA model (poster). 10th Symposium Pesticide Chemistry, Environmental Fate of Xenobiotics, Castelnuovo Fogliani (PC, Italy) 30/9-2/10/1996.

1995. Lega P, Libè A., Raggi C., Tonelli T., Marletto V., Zinoni F. Applicazione del modello CRITERIA a due aree test della provincia di Piacenza. Nota interna dell'Amm. Provinciale di Piacenza, pp. 70.

1995. Marletto V., Zinoni F., Tonelli T. Il progetto CRITERIA: un ambiente geografico per modellare il bilancio idrico di suoli coltivati. Atti del Congresso annuale AICA, Chia, Cagliari, 27-29/9/1995, 785-787.

1994. Marletto V., Zinoni F. CRITERIA: un modello per l'idrologia e la salvaguardia ambientale. Mensile AER, Servizio Meteorologico Regionale, Maggio 1994.

1993. Zinoni F. CRITERIA. Analisi delle fasi di realizzazione del modello e di gestione delle banche dati e delle informazioni nei programmi di assistenza tecnica e nella programmazione del territorio. Documento a cura di F. Zinoni, Novembre 1993.

1993. Marletto V., Zinoni F., Filippi N., Angelelli A., Laruccia N., Lega P., Tonelli T. CRITERIA: an integrated geographical system for soil water monitoring (poster summary). Proc. of the JRC-IRSA Conf. on the MARS project, Belgirate, 17-18/11/93.

1993. Marletto V., Zinoni F., Filippi N., Angelelli A., Laruccia N., Lega P., Tonelli T. CRITERIA: an integrated geo-graphical system for soil water monitoring. Proc. IX Symposium Pesticide Chemistry, Mobility and Degradation of Xenobiotics, Piacenza 12-13 october 1993, 695-706.

1993. Marletto V., Zinoni F. CRITERIA: un sistema geografico integrato per la simulazione del comportamento idrologico dei suoli. Atti del 1° convegno nazionale Fisica dell'Ambiente, Brescia, 15-17/12/93, 299-301.

1992. Marletto V., Zinoni F. Il progetto CRITERIA. Relazione preliminare. Bologna 10 Dicembre 1992.

Other references

Driessen P.M., 1986. *The water balance of the soil*. In: *Modeling of agricultural production: weather, soils and crops*. van Keulen, H., Wolf, J., (eds.), Pudoc, Wageningen, 479 pp.

Driessen P.M., Konijn N.T., 1992. Land-use systems analysis. Wageningen: Wageningen Agricultural University.

Hargreaves, G. H., & Samani, Z. A. (1985). Reference crop evapotranspiration from temperature. *Applied engineering in agriculture*, 1(2), 96-99.

Ippisch O., Vogel H.J., Bastian P., 2006. Validity limits for the van Genuchten–Mualem model and implications for parameter estimation and numerical simulation. *Adv Water Resour.*, 29: 1780–9.

Mualem Y., 1976. A new model for predicting the hydraulic conductivity of unsaturated porous media. *Water Resour. Res.*, 12: 513–22.

Van Genuchten MT., 1980. A closed-form equation for predicting the hydraulic conductivity of unsaturated soils. *Soil Sci. Soc. Am. J.*, 44: 892–8.